

```

#include <stdio.h>
#include <stdint.h>

///////////////////////////////
// Filter Code Definitions
///////////////////////////////

// maximum number of inputs that can be handled
// in one function call
#define MAX_INPUT_LEN    80
// maximum length of filter than can be handled
#define MAX_FLT_LEN      63
// buffer to hold all of the input samples
#define BUFFER_LEN        (MAX_FLT_LEN - 1 + MAX_INPUT_LEN)

// array to hold input samples
double insamp[ BUFFER_LEN ];

// FIR init
void firFloatInit( void )
{
    memset( insamp, 0, sizeof( insamp ) );
}

// the FIR filter function
void firFloat( double *coeffs, double *input, double *output,
              int length, int filterLength )
{
    double acc;          // accumulator for MACs
    double *coefffp; // pointer to coefficients
    double *inputp; // pointer to input samples
    int n;
    int k;

    // put the new samples at the high end of the buffer
    memcpy( &insamp[filterLength - 1], input,
            length * sizeof(double) );

    // apply the filter to each input sample
    for ( n = 0; n < length; n++ ) {
        // calculate output n
        coefffp = coeffs;
        inputp = &insamp[filterLength - 1 + n];
        acc = 0;
        for ( k = 0; k < filterLength; k++ ) {
            acc += (*coefffp++) * (*inputp--);
        }
        output[n] = acc;
    }
    // shift input samples back in time for next time
    memmove( &insamp[0], &insamp[length],
             (filterLength - 1) * sizeof(double) );
}

```

```

////////// Test program //////////
// bandpass filter centred around 1000 Hz
// sampling rate = 8000 Hz

#define FILTER_LEN 63
double coeffs[ FILTER_LEN ] =
{
    -0.0448093, 0.0322875, 0.0181163, 0.0087615, 0.0056797,
    0.0086685, 0.0148049, 0.0187190, 0.0151019, 0.0027594,
    -0.0132676, -0.0232561, -0.0187804, 0.0006382, 0.0250536,
    0.0387214, 0.0299817, 0.0002609, -0.0345546, -0.0525282,
    -0.0395620, 0.0000246, 0.0440998, 0.0651867, 0.0479110,
    0.0000135, -0.0508558, -0.0736313, -0.0529380, -0.0000709,
    0.0540186, 0.0766746, 0.0540186, -0.0000709, -0.0529380,
    -0.0736313, -0.0508558, 0.0000135, 0.0479110, 0.0651867,
    0.0440998, 0.0000246, -0.0395620, -0.0525282, -0.0345546,
    0.0002609, 0.0299817, 0.0387214, 0.0250536, 0.0006382,
    -0.0187804, -0.0232561, -0.0132676, 0.0027594, 0.0151019,
    0.0187190, 0.0148049, 0.0086685, 0.0056797, 0.0087615,
    0.0181163, 0.0322875, -0.0448093
};

void intToFloat( int16_t *input, double *output, int length )
{
    int i;

    for ( i = 0; i < length; i++ ) {
        output[i] = (double)input[i];
    }
}

void floatToInt( double *input, int16_t *output, int length )
{
    int i;

    for ( i = 0; i < length; i++ ) {
        // add rounding constant
        input[i] += 0.5;
        // bound the values to 16 bits
        if ( input[i] > 32767.0 ) {
            input[i] = 32767.0;
        } else if ( input[i] < -32768.0 ) {
            input[i] = -32768.0;
        }
        // convert
        output[i] = (int16_t)input[i];
    }
}

```

```

// number of samples to read per loop
#define SAMPLES    80

int main( void )
{
    int size;
    int16_t input[SAMPLES];
    int16_t output[SAMPLES];
    double floatInput[SAMPLES];
    double floatOutput[SAMPLES];
    FILE    *in_fid;
    FILE    *out_fid;

    // open the input waveform file
    in_fid = fopen( "input.pcm", "rb" );
    if ( in_fid == 0 ) {
        printf("couldn't open input.pcm");
        return;
    }

    // open the output waveform file
    out_fid = fopen( "outputFloat.pcm", "wb" );
    if ( out_fid == 0 ) {
        printf("couldn't open outputFloat.pcm");
        return;
    }

    // initialize the filter
    firFloatInit();

    // process all of the samples
    do {
        // read samples from file
        size = fread( input, sizeof(int16_t), SAMPLES, in_fid );
        // convert to doubles
        intToFloat( input, floatInput, size );
        // perform the filtering
        firFloat( coeffs, floatInput, floatOutput, size,
                  FILTER_LEN );
        // convert to ints
        floatToInt( floatOutput, output, size );
        // write samples to file
        fwrite( output, sizeof(int16_t), size, out_fid );
    } while ( size != 0 );

    fclose( in_fid );
    fclose( out_fid );

    return 0;
}

```